

# Euroengel

## Professional mobile refrigeration

|                 |                                                                                    |                                                                                                                                                  |                                                                                                                         |                                                                                                                                                                                                                               |                                                                                      |                                    |
|-----------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|------------------------------------|
| T0022 FDN -24°C |   | <b>Top Loader - 22 Lt</b><br>-24°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz<br>65-70 mm PU K<0,40 Wm/K<br>15 kg |  59 cm 38 cm 48 cm 29 cm 23 cm 35 cm   | <b>Top Loader - 140 Lt</b><br>FDN: -10°C (+30°C T <sub>int</sub> )<br>FDN: -24°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A (18-8 A)<br>100-240Vac 1,6-0,8 A (3-1,5 A) 50-60 Hz<br>80-100 mm PU K<0,40 Wm/K<br>32 kg (37 kg) |   | T0140 NDN -10°C<br>T0140 FDN -24°C |
| T0032 FDN -24°C |   | <b>Top Loader - 32 Lt</b><br>-24°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz<br>65-70 mm PU K<0,40 Wm/K<br>17 kg |  67 cm 39 cm 48 cm 36 cm 25 cm 35 cm   | <b>Top Loader - 330 Lt</b><br>FDN: -10°C (+30°C T <sub>int</sub> )<br>FDN: -21°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A (18-8 A)<br>100-240Vac 1,6-0,8 A (3-1,5 A) 50-60 Hz<br>100 mm PU K<0,40 Wm/K<br>84 kg (94 kg)    |   | T0330 NDN +1°C<br>T0330 FDN -21°C  |
| T0056 FDN -24°C |   | <b>Top Loader - 56 Lt</b><br>-24°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz<br>70 mm PU K<0,40 Wm/K<br>19 kg    |  80 cm 50 cm 50 cm 45 cm 33 cm 35 cm   | <b>Front opening - 140 Lt</b><br>FDN: -10°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz<br>80-100 mm PU K<0,40 Wm/K<br>32 kg                                                                    |   | F0140 NDN -10°C                    |
| T0082 FDN -24°C |  | <b>Top Loader - 82 Lt</b><br>-24°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz<br>80 mm PU K<0,40 Wm/K<br>29 kg    |  94 cm 56 cm 55 cm 54 cm 37 cm 36 cm | <b>Front opening - 330 Lt</b><br>FDN: +1°C (+30°C T <sub>int</sub> )<br>12-24Vdc 9-4 A 100-240Vac 1,6-0,8 A 50-60 Hz<br>100 mm PU K<0,40 Wm/K<br>80 kg                                                                        |  | F0330 NDN +1°C                     |

## The cold chain on the move!



[www.euroengel.it](http://www.euroengel.it)